



Â  
Â  
Â  
Â Withstand Voltage:  
Â 300VAC max.  
Â

Both adapter cables are constructed ofÂ  
Â  
Â  
Insulation Resistance:  
500 MÂ€ŽÂ! min.  
Â

0.8mm diameter, single shielded coaxial  
Â  
Â  
Operating  
Â  
-40Â° C to +90Â°CÂ  
Â

cable and are 130mm long. Typically the FMEÂ  
Â  
Temperature Range:  
Â  
Â

cable is used with GSM/CDMA antennas,  
Â  
Â  
Humidity:  
Â  
90% max,  
Â

while the SMA cable is used for GPS antennas.Â  
Â  
Â  
non-condensing  
Â

Â  
Â  
Â  
Â  
Â  
Â  
Â

Â  
Â  
Â  
Â

Connector Body Materials:

Â

Features Include:

Â  
Â  
Â  
Â Â Â Â Â Â Â Connector  
Â Â Â Â Â Â Â Material  
Â

Â  
Â  
Â  
Â  
SMA  
Â  
Gold plated brass  
Â

Â Â Â Â High flexibility  
Â  
Â  
Â  
FME  
Â  
Nickel plated brass  
Â

Â Â Â Â Excellent RF characteristics  
Â  
U.FL  
Â  
Silver plated bronze  
Â  
Â

Â Â Â Â Wide operating temperature range  
Â  
Â  
Â  
Â  
Â  
Â

Â  
Â  
Â  
Â  
Â  
Â  
Â

Â  
Â  
Â  
Â  
Â

Â  
Â  
Â

Mounting Requirements:

Â  
Â

Ordering Information:

Â  
Â

Connector

Value

Â  
Â

Part Number

Bulkhead Connector Type

Â

SMA

0.25" (6.4mm) D-hole

Â  
Â  
Â  
Â  
Â

FME

0.39" (10mm) hole

Â  
Â

10001710

SMA Bulkhead Jack

Â

Â  
Â

Â  
Â

10001711

FME Bulkhead Male

Â \*Other connectors and cable lengths available upon request

Â  
Â  
Â  
Â  
Â

Â  
Â

Â  
Â

Â  
Â

(data sheet)